

NAME

rmpr - remove a project

SYNOPSIS

rmpr [-fsv] project

PARAMETERS

project The project to be removed.

OPTIONS

Options are:

- f** Force removal of cells in project.
- s** Silence(sure) mode (don't ask for it).
- v** Verbose mode. More verbose, if used more than ones.

DESCRIPTION

Rmpr removes the specified *project*. The argument has to be a legal UNIX path to the project directory.

With the -f option *rmpr* removes all cells in the project. If the -f option is not specified *rmpr* requires the project to be empty, that is, it should contain no cells.

The project directory is removed only if it does not contain any non-project files. If it does contain non-project files *rmpr* just degrades the project directory to an ordinary non-project directory containing only the remaining non-project files.

NOTE

This program does not use environment variable CWD.

EXAMPLES

```
% rmpr old_project
% rmpr ../../projects/project3
```

AUTHORS

P. van der Wolf, P. Bingley.

FILES

The following files and directories are removed:

project/.dmrc	(file)
project/.dmxdata	(file)
project/projlist	(file)
project/exp_dat	(file)
project/display.out	(Xspace file)
project/layout	(view dir.)
project/circuit	(view dir.)
project/floorplan	(view dir.)
project/seadif	(ocean dir.)
project/sls_prototypes	(ocean dir.)
project	(project dir.)
project/.cslsrc	(init file)
project/.dalirc	(init file)
project/.seadalirc	(init file)
project/.simeyerc	(init file)
project/.space.def.p	(init file)

SEE ALSO

mkpr(1ICD), rmdb(1ICD).

DIAGNOSTICS

Upon successful completion *rmpr* returns exit code 0. Otherwise, a diagnostic is printed and 1 is returned.