

NAME

rmdb - remove cell parts of an ICD database project

SYNOPSIS

rmdb [-aifv] [-c *cellname*] [-p *project*] [layout] [circuit] [floorplan]

OPTIONS

- a** Remove *all* cells of all views, if not further restricted by the **-c** option or one or more view specifications.
- i** Clean also *impcelllist* of views. Not allowed in combination with the **-c** option.
- f** Use *force* mode: no confirmations are asked.
- v** Use *verbose* mode.
- c** Remove *cell* with name <cellname> from database. Either the **-a** option (for all views) or one or more view specifications must be given.
- p** Use this *project* path for the database removals.

DESCRIPTION

Rmdb can clean a complete ICD database or remove parts from it. It can remove all cells from one or more views together.

Rmdb can also remove individual cells from one or more views.

Rmdb asks for a confirmation, when option **-f** is not specified, before proceeding.

NOTES

The current working directory must be the project directory.
You can use the environment variable CWD.

EXAMPLES

```
% rmdb -aiv
```

The above example removes verbose *all* cells from *all* views and cleans also the "impcelllist" in the views.

```
% rmdb layout circuit
```

The above example removes *all* cells from the layout and circuit view.

```
% rmdb -c FlipFlop layout
```

The above example removes the FlipFlop cell from the layout view.

```
% rmdb -c FlipFlop -c nand2 -af
```

The above example removes the FlipFlop and nand2 cell from *all* views and does not ask for it.

AUTHORS

S. de Graaf

FILES

project/exp_dat	(removed, if layout view)
project/display.out	(removed, if layout view)
project/view/celllist	(cleaned)
project/view/impcelllist	(cleaned, option -i)
project/view/cell ...	(removed)

DIAGNOSTICS

Generally self-explanatory. All messages are echoed on the *stderr* output.